

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
4 July 2002 (04.07.2002)

PCT

(10) International Publication Number
WO 02/051530 A1(51) International Patent Classification⁷: **B01F 3/04**

[US/US]; Fluor Corporation, One Fluor Daniel Drive, Aliso Viejo, CA 92656-2606 (US).

(21) International Application Number: PCT/US01/13436

(22) International Filing Date: 24 April 2001 (24.04.2001)

(74) Agent: **FISH, Robert, D.**; Fish & Associates, LLP, Suite 706, 1440 N. Harbor Boulevard, Fullerton, CA 92835 (US).

(25) Filing Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(26) Publication Language: English


(30) Priority Data:
60/257,414 21 December 2000 (21.12.2000) US(71) Applicant (*for all designated States except US*): **FLUOR CORPORATION** [US/US]; One Enterprise Drive, Aliso Viejo, CA 92656-2606 (US).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **JACOBS, Garry, E.** [US/US]; Fluor Corporation, One Fluor Daniel Drive, Aliso Viejo, CA 92656-2606 (US). **STUPIN, Steven, W.** [US/US]; Fluor Corporation, One Fluor Daniel Drive, Aliso Viejo, CA 92656-2606 (US). **MILLIKEN, Adam, S.**(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHODS AND APPARATUS FOR MIXING FLUIDS



(57) Abstract: A bubble cap (100) has a riser (120) and a cap (130), separated by a divider (140) that extends to a length at least 50 % of a distance measured between the top of the riser (122) and the bottom of the cap (134). In another aspect, the riser (120) and cap (130) cooperate to provide a skirt height (160) of no less than 1.5". More preferred bubble caps (400) have a relatively high skirt height (460) or long slit length (497), or both. In yet another aspect, flow-redirecting vanes (610) and plates (630) cooperate to provide a rough distribution of fluids to subsequent distribution tray (650).

WO 02/051530 A1